

# Multiphase-Tolerant Turbine (MuTT) Development for an sCO<sub>2</sub> PTES System

**Natalie R. Smith**

Contributions from: Cole Replogle, Reese Roddy, Zachary Brown, Coleen McCandless, Douglas Hofer, Kaitlyn Witt, Mark Anguiano, Subhra Shanka Koley  
*Southwest Research Institute, San Antonio, TX, USA*

Thermal, Mechanical, and Chemical Energy Storage Workshop  
July 30, 2025



# Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or Implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



**Award No. DE-EE0009815**

Office of Energy Efficiency and Renewable Energy  
under the Solar Energy Technologies Office


**Project Partners:**

Echogen & Flowserve




# Why is a cold turbine difficult?


- **Multiphase flow!**
- Lack of validation data for loss models in this flow regime [3-5]
- Lack of turbine design experience in the open literature [6-7]



a) Transient two-phase flow.



b) Separated two-phase flow.




c) Dispersed two-phase flow.


[3]



[6]




[4]



[7]

## Various examples of sCO<sub>2</sub> heat pumps



# Multiphase Tolerant Turbine (MuTT) Project Overview

Project Objective:

***Retire multiphase turbine design risks through an understanding of multiphase turbine operation, enabling improved turbine performance and operability range***

## BP1 – Design

1. Turbine design
2. Multiphase CO2 modeling validation data
3. Test loop design

**This presentation will highlight our most significant challenge in the loop design & initial multiphase data**


## BP2 – Procurement & Assembly

1. Procurement
2. Assembly
3. Commissioning

Waiting for BP2 approval

## BP3 – Testing


1. Testing
2. Data processing



For Scaled Turbine Test in BP3

# MUTT LOOP DESIGN


# Turbine Test Loop Arrangement



# Test Loop Conditions Definition

Two key challenges arose after initial sweeps of test conditions:



- 1) confidence in pressure loss modeling
- 2) the large required thermal duty for heat rejection



# Estimating heat rejection requirement with gross assumptions of pressure losses...

**Assume:**

1. Neglect pressure loss in the piping
2. Minimal pressure loss through the HX
3. No subcooling







# Estimating heat rejection requirement with gross assumptions of pressure losses...

**Assume:**



- 1. Neglect pressure loss in the piping**
- 2. Minimal pressure loss through the HX**
- ~~3. No subcooling~~ **5 °C subcooling**



# Estimating heat rejection requirement with gross assumptions of pressure losses...

**Assume:**



1. Neglect pressure loss in the piping
2. Minimal **15%** pressure loss through the HX
3. No subcooling **5 °C subcooling**



# Estimating heat rejection requirement with gross assumptions of pressure losses...

## Assume:

1. Neglect **Multiphase** pressure loss in the piping
2. Minimal **15%** pressure loss through the HX
3. No subcooling **5 °C subcooling**




# Assumptions of pressure losses underestimated the required cooling duty by **0.6 MWth**

## Assume:

1. Neglect **Multiphase** pressure loss in the piping
2. Minimal **15%** pressure loss through the HX
3. No subcooling **5 °C subcooling**

*These are all assumptions easily made during proposal and rough order of magnitude checks and led to a large miss in test requirements.*


*Highlighted the need for multiphase CO<sub>2</sub> validation data for not only the turbine design, but also the loop design*






# MULTIPHASE NOZZLE TESTING


# A converging-diverging nozzle design selected pressure loss and multiphase CFD validation data




1. Liquid at inlet and expand to the highest vapor fraction possible



2. Inlet design to accommodate measurability and manufacturability




3. Throat was made as long as possible, and the diverging section was made linear and long enough to prevent flow separation








# Detailed nozzle instrumentation included:




2x Gamma-ray densitometers



# Multiphase flow was confirmed through an isenthalpic process assumption and densitometer data




**Pressure data showed pressure drops between 4.0-9.6 bar**




**Quality estimated from isenthalpic process**



# Multiphase flow was confirmed through an isenthalpic process assumption and densitometer data




**Density estimated from  
isenthalpic process**



**Density measurements from  
densitometer**

# The Lockhart-Martinelli multiphase pressure drop model is much more appropriate than homogenous Darcy-Weisbach



## Homogenous Model: Darcy-Weisbach [9]

$$\Delta P_{total} = \int_0^L f(x) \frac{dx}{D(x)} \frac{\rho(x)v(x)^2}{2}$$

$f$  = Darcy friction factor

$L$  = pipe length

$D$  = pipe diameter



$\rho$  = fluid mixture density

$v$  = fluid mixture velocity

## Lockhart-Martinelli Model [10]: Two-phase pressure drop multiplier

$$\phi_{lo}^2 = 1 + \frac{20}{X} + \frac{1}{X^2}$$

$$X = \sqrt{\left(\frac{f}{2D}\right) \cdot \frac{(1 - VMF)^2}{VMF^2} \cdot \left(\frac{\rho_v}{\rho_l}\right)}$$



STEP, Oxy-combustion, Comander with IGV

## OTHER SCO<sub>2</sub> TESTING ACCOMPLISHMENTS



# STEP sCO<sub>2</sub> Technology Maturation Achievements



- Successfully demonstrated gas-fired indirect sCO<sub>2</sub> plant operation at 500 °C simple recuperated cycle “max” conditions generating ~4 MW net power while grid-synchronized
- All major components commercially procured except turbine jointly designed by GE Vernova and SwRI:
  - Compressors: Baker Hughes
  - Heat Exchangers: Parker Heatric, Optimus, Vacuum Process Engineering
  - Heater Protection Valve and 500 °C Turbine Trip Valve: SchuF, AVS/HORA
  - Plant Controller: GE Mark VI
- Demonstrated repeatability through multiple operations, also safely demonstrated fast and slow trips
- Project Partners:



- Plant design details available to JIP members



*Thank you*

**Natalie R. Smith, Ph.D.**  
Manager, R&D  
natalie.smith@swri.org

GT2025-154034



**The Design of a Multiphase CO<sub>2</sub> Turbine Test Facility**



GT2025-154157

**Experimental Investigation of Vapor Formation in Liquid  
CO<sub>2</sub> Flow Through a Converging-Diverging Nozzle**

**ECHOGEN**  
power systems



# References

1. McTigue, Farres-Antunez, Ellingwood, Neises, White, 2020, "Pumped thermal electricity storage with supercritical CO<sub>2</sub> cycles and solar heat input," *AIP Conference Proceedings* 2303, 190024.
2. Aga, V., Conte, E., Carroni, R., Burcker, B., & Ramond, M. (2016, March). Supercritical CO<sub>2</sub>-based heat pump cycle for electrical energy storage for utility scale dispatchable renewable energy power plants. *In Proc: 5th Int. Symp.—Supercritical CO<sub>2</sub> Power Cycles* (San Antonio, United States).
3. Wikipedia, "Two-Phase Flow," [https://en.m.wikipedia.org/wiki/Two-phase\\_flow](https://en.m.wikipedia.org/wiki/Two-phase_flow)
4. Supak, Kevin, et al. "Two-Phase CO<sub>2</sub> Flow Behavior in Horizontal Piping." *International Pipeline Conference*. Vol. 88582. American Society of Mechanical Engineers, 2024.
5. Lettieri, Claudio, et al. "Characterization of nonequilibrium condensation of supercritical carbon dioxide in a de laval nozzle." *Journal of Engineering for Gas Turbines and Power* 140.4 (2018): 041701.
6. Kaupert, Kevin, et al. "Flashing liquid expanders for LNG liquefaction trains." *Proceedings of 17th International Conference & Exhibition on Liquefied Natural Gas (LNG 17)*. Gas Technology Institute (GTI), Houston, USA. (2013).
7. Hosangadi, Ashvin, et al. "Numerical Predictions of Mean Performance and Dynamic Behavior of a 10 MWe SCO<sub>2</sub> Compressor With Test Data Validation." *Journal of Engineering for Gas Turbines and Power* 144.12 (2022): 121019.
8. <https://nfgm.no/wp-content/uploads/2019/02/2009-05-X-ray-based-densitometer-for-multiphase-flow-measurement-Tjugum-Roxar.pdf>
9. Moody, L. F., "Friction Factors for Pipe Flow," *Transactions of the ASME*, 66, 8, November 1944, pp. 671-684.
10. Lockhart, R. W.; Martinelli, R. C. (1949). "Proposed correlation of data for isothermal two-phase, two-component flow in pipes". *Chemical Engineering Progress*. 45: 39–48